

**Aluminium-Spray A-400****! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Name of product Aluminium-Spray A-400
Code-Nr. 110510

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

Technical Aerosols

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG
Königsberger Str. 255,, DE-48157 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone ++49(0)251 / 9322 - 0
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229	
Eye Irrit. 2	H319	
STOT SE 3	H336	
Aquatic Chronic 3	H412	

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07

Signal word

Danger

Hazard Statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

acetone

Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Product has an anesthetic effect.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Aluminium coloured laquer based on synthetic resin solvent and pigments.

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-64-1	200-662-2	acetone	15 < 20	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
74-98-6	200-827-9	propane	20 < 25	Flam. Gas 1, H220 / Press. Gas
106-97-8	203-448-7	butane	20 < 25	Flam. Gas 1, H220 / Press. Gas
123-86-4	204-658-1	n-butyl acetate	< 10	Flam. Liq. 3, H226 / STOT SE 3, H336
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom. (NOTA P)	10 < 15	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335 / Aquatic Chronic 2, H411 / STOT SE 3, H336 / , EUH066
92045-53-9	295-434-2	Naphtha (petroleum), hydrodesulfurized light, dearomatized	2,5 < 5	Flam. Liq. 2, H225 / Skin Irrit. 2, H315 / Asp. Tox., H304 / Aquatic Chronic 2, H411 / STOT SE 3, H336
7429-90-5	231-072-3	Aluminium	< 10	Flam. Sol. 1, H228
64742-48-9	265-150-3	Naphtha (petroleum), hydrotreated heavy	1 < 10	Asp. Tox. 1, H304
64742-49-0	265-151-9	Naphtha (petroleum), hydrotreated light	1 < 2,5	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411

REACH

CAS No	Name	REACH registration number
7429-90-5	Aluminium	01-2119529243-45

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.



4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

The following symptoms may occur:

Unconsciousness
Anaesthetic state
Headache
Confusion
Dizziness

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam
Dry fire-extinguishing substance
Carbon dioxide
sand

Unsuitable extinguishing media

water
Full water jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting
In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.
Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.
Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material.
After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7
Disposal: see section 13
Personal protection equipment: see section 8



SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale aerosols

Hygiene measures

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn even after use.

Protect from heat and sunlight.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Store at +5 till +25 °C.

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Store in a dry place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
67-64-1	Acetone	8 hours	1210	500	EH40/2005
		Short-term	3620	1500	
7429-90-5	Aluminium metal: inhalable dust	8 hours	10		EH40/2005
7429-90-5	Aluminium metal: respirable dust	8 hours	4		EH40/2005
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
109-87-5	Dimethoxymethane	8 hours	3160	160	EH40/2005
		Short-term	3950	1250	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.6

Aluminium-Spray A-400**Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
67-64-1	acetone	8 hours	1210	500	

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
123-86-4	n-butyl acetate	480 mg/m3	DNEL long-term inhalative (systemic)	
		960 mg/m3	DNEL acute inhalative (local)	
		960 mg/m3	DNEL acute inhalative (systemic)	
		480 mg/m3	DNEL long-term inhalative (local)	
64742-95-6	Solvent naphtha (petroleum), light arom. (NOTA P)	150 mg/m3	DNEL long-term inhalative (systemic)	
		25 mg/kg	DNEL long-term dermal (systemic)	
67-64-1	acetone	1210 mg/m3	DNEL long-term inhalative (systemic)	
		2420 mg/m3	DNEL acute inhalative (local)	
		186 mg/kg	DNEL long-term dermal (systemic)	

DNEL Consumer

CAS No	Substance name	Value	Code	Remark
64742-95-6	Solvent naphtha (petroleum), light arom. (NOTA P)	11 mg/kg	DNEL long-term oral (repeated)	

PNEC

CAS No	Substance name	Value	Code	Remark
123-86-4	n-butyl acetate	0,018 mg/l	PNEC aquatic, marine water	
		0,981 mg/kg	PNEC sediment, freshwater	
		0,18 mg/l	PNEC aquatic, freshwater	
67-64-1	acetone	3,04 mg/kg	PNEC sediment, marine water	
		1,06 mg/l	PNEC aquatic, marine water	
		30,4 mg/kg	PNEC sediment, freshwater	
		10,6 mg/l	PNEC aquatic, freshwater	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles

**Aluminium-Spray A-400****Other protection measures**

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

aerosol

Colour

grey

Odour

characteristic

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 200 °C				estimate
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined	20 °C			
Relative density	not determined				
Vapour density	not determined				
Solubility in water	not determined				
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				

**Aluminium-Spray A-400**

	Value	Temperature	at	Method	Remark
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products**Thermal decomposition**

Remark No decomposition if used as directed.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LC50 acute inhalation	> 5 mg/l (4 h)	rat		Aluminium
Skin irritation	irritant			
Eye irritation	irritant			

Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

When inhaled, reaction time and coordination sense may be reduced.

Product may cause irreversible eye injuries.

Inhalation causes headache/nausea.

Irritates eyes and skin.



Inhalation causes narcotic effect/intoxication.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

16 05 04*

Name of waste

gases in pressure containers (including halons) containing hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable

**Aluminium-Spray A-400**

	ADR/RID	IMDG	IATA-DGR
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not applicable**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

Transport as limited quantities according to 3.4 IMDG Code is possible.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 83,6 %

VOC value 595 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.5

EUH066 Repeated exposure may cause skin dryness or cracking.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H228 Flammable solid.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.6

Aluminium-Spray A-400

H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.