

No. 1907/2006 (REACH)
Printed 11.01.2016

revision 17.07.2015 (GB) Version 8.6

AT-44 Allround-Spray

# ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product AT-44 Allround-Spray
Code-Nr. 112500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

**Technical Aerosols** 

1.3. Details of the supplier of the safety data sheet

**Distributor** WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster Postbox 48045, DE-8460 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

Emergency advice -

Phone -

GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)

Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories

Hazard Statements Classification procedure

Aerosol 1 H222, H229 STOT SE 3 H336

**Hazard Statements** 

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.



No. 1907/2006 (REACH)
Printed 11.01.2016

revision 17.07.2015 (GB) Version 8.6

AT-44 Allround-Spray

#### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS02

GHS07

# Signal word

Danger

#### **Hazard Statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

#### **Precautionary Statements**

P102	Keep out of reach of children.
P210 P211 P251 P261 P271	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.  Avoid breathing dust/fume/gas/mist/vapours/spray.  Use only outdoors or in a well-ventilated area.
P304 + P340 P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
P403 + P233 P405 P410 + P412	Store in a well-ventilated place. Keep container tightly closed.  Store locked up.  Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

# 2.3. Other hazards

## Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

# Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

not applicable

# 3.2. Mixtures

#### Description

Mixture of active ingredients with propellant

# **Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
95-63-6	202-436-9	1,2,4-trimethylbenzene	0,1 - 0,29	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Eye Irrit. 2, H319 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Aquatic Chronic 2, H411
64742-47-8	265-149-8	Distillates (petroleum), hydrotreated light; Kerosine - unspecified	10 - 24,99	Asp. Tox. 1, H304



No. 1907/2006 (REACH)
Printed 11.01.2016

revision 17.07.2015 (GB) Version 8.6

# AT-44 Allround-Spray

CAS No	EC No	Name	[%	Classification according to Regulation (EC)
			weight]	No 1272/2008 [CLP/GHS]
64742-48-9	919-857-5	Naphtha (petroleum), hydrotreated heavy	10-24.99	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT
				SE 3, H335 / , EUH066
	polymer	Alkaryl polyether	0,3 - 0,99	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Aquatic Chronic 2, H411
REACH				
CAS No	Name			REACH registration number
64742-48-9	Nanhtha (net	roleum), hydrotreated heavy		01-211946325833-xxxx

#### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

# In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

#### In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

# Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

water mist

## Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

#### 5.3. Advice for firefighters



No. 1907/2006 (REACH)
Printed 11.01.2016

revision 17.07.2015 (GB) Version 8.6

AT-44 Allround-Spray

# Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

#### **Additional information**

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

#### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

#### 6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

## Advice on safe handling

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

#### General protective measures

Do not inhale aerosols

#### Hygiene measures

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Avoid effect of heat.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.



No. 1907/2006 (REACH)
Printed 11.01.2016

revision 17.07.2015 (GB) Version 8.6

AT-44 Allround-Spray

#### Further information on storage conditions

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

#### 7.3. Specific end use(s)

# Recommendation(s) for intended use

See section 1.2

# ! SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	

#### Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
95-63-6	1,2,4-trimethylbenzene	8 hours	100	20	

#### Additional advice

The statutory local and national regulations have to be observed.

#### 8.2. Exposure controls

### Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short term: filter apparatus, Filter A/P2

#### ! Hand protection

Gloves (solvent-resistant)

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification: Nitile rubber

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

#### Eye protection

tightly fitting goggles

## Other protection measures

protective clothing

#### Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

AppearanceColourOdouraerosolyellowishcharacteristic

**Odour threshold** 



No. 1907/2006 (REACH)
Printed 11.01.2016

revision 17.07.2015 (GB) Version 8.6

AT-44 Allround-Spray

not determined

Important health, safety and environmental information

Value Temperature Method Remark at not determined pH value not applicable boiling point **Melting point / Freezing** not determined point not applicable Aerosol Flash point not determined Vapourisation rate Flammable (solid) not applicable Flammability (gas) not determined 200 °C Ignition temperature The product is not Self ignition temperature self-igniting. Lower explosion limit 0,5 Vol-% 10,9 Vol-% **Upper explosion limit** Vapour pressure 2100 hPa 20 °C 20 °C Relative density 0,75 g/cm3 not determined Vapour density No or low immiscibility Solubility in water not determined Solubility/other Partition coefficient nnot determined octanol/water (log P O/W) not determined **Decomposition** 

Viscosity

temperature

not determined

Solvent content

0-11-1- ---4---4

59,1 %

Solids content

34,3 %

# Oxidising properties

No information available.

# **Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated



No. 1907/2006 (REACH)
Printed 11.01.2016

revision 17.07.2015 (GB) Version 8.6

AT-44 Allround-Spray

#### 9.2. Other information

No information available.

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

No information available.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known.

#### 10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

#### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

## Thermal decomposition

Remark No decomposition if used as directed.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark	
	value/ validation	Оресіез	Wethod	Remark	
LD50 acute oral	> 5000 mg/kg	rat		Naphtha	
LD50 acute dermal	> 5000 mg/kg	rabbit		Naphtha	
LC50 acute inhalation	4951 mg/m3 (4 h)	rat		Naphtha	
Skin irritation	non-irritant				
Eye irritation	non-irritant				
Skin sensitization	non-sensitizing				

## **Experiences made from practice**

Vapours may cause dizziness, headaches and tiredness

# Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.



No. 1907/2006 (REACH)
Printed 11.01.2016

revision 17.07.2015 (GB) Version 8.6

AT-44 Allround-Spray

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

#### **Ecotoxicological effects**

	Value	Species	Method	Validation	
Fish	LL/EL/IL50 > 1000 mg/l (96 h)	Oncorhynchus mykiss		Naphtha	
Daphnia	LL/EL/IL50 1000 mg/l (48 h)	Daphnia magna		Naphtha	
Algae	LL/EL/IL50 > 1000 mg/l (72 h)	Pseudokirchneriella subcapitata		Naphtha	

#### 12.2. Persistence and degradability

No information available.

#### 12.3. Bioaccumulative potential

No information available.

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

# **General regulation**

07 01 04\*

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Name of waste

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste code No.

other organic solvents, washing liquids and mother liquors

20 01 99 other fractions not otherwise specified

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

#### Recommendations for the product

Remove in accordance with local official regulations.

# Recommendations for packaging

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

#### **General information**

For proper waste disposal a complete emptying of the tin is necessary.

# **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950



No. 1907/2006 (REACH)
Printed 11.01.2016

revision 17.07.2015 (GB) Version 8.6

# AT-44 Allround-Spray

	ADR/RID	IMDG	IATA-DGR
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

### 14.6. Special precautions for user

Caution: Gases

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

#### Land and inland navigation transport ADR/RID

Hazard label(s) 2.1 tunnel restriction code D Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

# ! SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC** standard

**VOC content** 59,05 % **VOC value** 443,1 g/L

### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

# ! SECTION 16: Other information

#### ! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

#### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.5

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.