

**Cockpit Spray****! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** Cockpit Spray  
Code-Nr. 114000

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended intended purpose(s)**

Technical Aerosols

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255,, DE-48157 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone ++49(0)251 / 9322 - 0  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

**Hazard Statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

**Cockpit Spray**

H411 Toxic to aquatic life with long lasting effects.

**2.2. Label elements****Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]**

GHS02



GHS07



GHS09

**Signal word**

Danger

**Hazard Statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**Precautionary Statements**

P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P362 Take off contaminated clothing.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container to hazardous or special waste collection point.

**Hazardous ingredients for labeling**

Hydrocarbons, C6, isoalkanes, <5% n-hexane, Naphtha (petroleum), hydrotreated light

**Special rules for supplemental label elements for certain mixtures**

Contains (R)-p-Mentha-1,8-dien. May produce an allergic reaction.

**2.3. Other hazards**

Product has an anesthetic effect.

**Information pertaining to special dangers for human and environment**

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/ information on ingredients

### 3.1. Substances

not applicable

### 3.2. Mixtures

#### Description

Mixture of active ingredients with propellant

#### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
75-28-5	200-857-2	isobutane	1 - 10	Flam. Gas 1, H220 / Press. Gas
106-97-8	203-448-7	butane	20 - 30	Flam. Gas 1, H220 / Press. Gas
5989-27-5	227-813-5	(R)-p-mentha-1,8-diene	0,5 - 1	Flam. Liq. 3, H226 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
74-98-6	200-827-9	propane	1 - 10	Flam. Gas 1, H220 / Press. Gas
64742-49-0	931-254-9	Hydrocarbons, C6, isoalkanes, <5% n-hexane	20 - 30	Flam. Liq. 2, H225 / Asp. Tox, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336
64742-49-0	921-024-6	Naphtha (petroleum), hydrotreated light	20 - 30	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336
90622-57-4	918-167-1	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	1 - 10	Asp. Tox. 1, H304 / Aquatic Chronic 4, H413

#### REACH

CAS No	Name	REACH registration number
74-98-6	propane	01-2119486944-21
64742-49-0	Hydrocarbons, C6, isoalkanes, <5% n-hexane	01-2119484651-34
64742-49-0	Naphtha (petroleum), hydrotreated light	01-2119475514-35

#### Labelling for contents according to regulation (EC) No 648/2004, annex VII

30 % and more aliphatic hydrocarbons

Scents ((R)-p-Mentha-1,8-dien, CITRAL)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

#### In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

#### In case of ingestion

If swallowed seek medical advice immediately and show the doctor packing or label.



## Cockpit Spray

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Dry powder

Carbon dioxide

sand

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

#### Additional information

Cool endangered containers with water spray jet.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and material for containment and cleaning up

Protect from water.

Disposal according to regulations.

Take up with absorbent material.

### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

**Cockpit Spray****SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**General protective measures**

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Protect from heat and sunlight.

Vapours can form an explosive mixture with air.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

**Advice on storage compatibility**

Do not store together with food.

**Further information on storage conditions**

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	

**DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
64742-49-0	Naphtha (petroleum), hydrotreated light	2035 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	
		773 mg/kg bw/day	DNEL long-term dermal (systemic)	



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.6

## Cockpit Spray

### DNEL Consumer

CAS No	Substance name	Value	Code	Remark
64742-49-0	Naphtha (petroleum), hydrotreated light	699 mg/kg bw/day	DNEL long-term dermal (systemic)	
		699 mg/kg bw/day	DNEL long-term oral (repeated)	
		608 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	

### Additional advice

The statutory local and national regulations have to be observed.

### 8.2. Exposure controls

#### Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

#### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

#### Eye protection

tightly fitting goggles

#### Other protection measures

protective clothing

#### Appropriate engineering controls

Sufficient ventilation and exhaustion.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

aerosol

#### Colour

colourless

#### Odour

characteristic

#### Odour threshold

not determined

### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	not applicable				
<b>Melting point / Freezing point</b>	not determined				
<b>Flash point</b>	not applicable				Aerosol
<b>Vapourisation rate</b>	not determined				



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.6

**Cockpit Spray**

	Value	Temperature	at	Method	Remark
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	200 °C				
<b>Self ignition temperature</b>					The product is not self-igniting.
<b>Lower explosion limit</b>	1 Vol-%				
<b>Upper explosion limit</b>	7,4 Vol-%				
<b>Vapour pressure</b>	3200 kPa				
<b>Relative density</b>	0,64 g/cm <sup>3</sup>	20 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>					No or low immiscibility
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity</b>	not determined				
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .				
<b>9.2. Other information</b>	No information available.				

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No information available.

**10.4. Conditions to avoid**

No information available.

**10.5. Incompatible materials**

No information available.

**Cockpit Spray****10.6. Hazardous decomposition products****Thermal decomposition**

Remark No decomposition if used as directed.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	4400 mg/kg	rat		(R)-p-Mentha-1,8-diene
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	non-irritant			
<b>Skin sensitization</b>	non-sensitizing			

**Experiences made from practice**

Irritates mucous membranes.

Inhalation causes narcotic effect/intoxication.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

**SECTION 12: Ecological information****12.1. Toxicity**

No information available.

**12.2. Persistence and degradability**

No information available.

**12.3. Bioaccumulative potential**

No information available.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****General regulation**

Toxic to aquatic life, fishes and plankton.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.



**Cockpit Spray****SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste code No.**

15 01 04

15 01 10\*

**Name of waste**

metallic packaging

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**General information**

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	<b>ADR/RID</b>	<b>IMDG</b>	<b>IATA-DGR</b>
<b>14.1. UN number</b>	1950	1950	1950
<b>14.2. UN proper shipping name</b>	AEROSOLS	AEROSOLS (NAPHTHA (PETROLEUM))	Aerosols, flammable
<b>14.3. Transport hazard class(es)</b>	2.1	2.1	2.1
<b>14.4. Packing group</b>	-	-	-
<b>14.5. Environmental hazards</b>	Yes	Yes	Yes

**14.6. Special precautions for user**

Caution: Gases

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**Land and inland navigation transport ADR/RID**

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

**Marine transport IMDG**

MARINE POLLUTANT

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard**

VOC content 94,35 %

VOC value 602 g/L



---

## 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

---

## SECTION 16: Other information

### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

### Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.5

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.