

No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product W 44 T Multi-Oil Code-Nr. 152510

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Liquids

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255,, DE-48157 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Flam. Liq. 3 H226 STOT SE 3 H336 Asp. Tox. 1 H304

Hazard Statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

2.2. Label elements



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]







GHS02

GHS07

GHS08

Signal word

Danger

P102

Hazard Statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Keep out of reach of children.

H336 May cause drowsiness or dizziness.

Precautionary Statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303 + P361 + IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

P353 water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use extinguishing powder or sand for extinction.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

Naphtha (petroleum), hydrotreated heavy

Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

Description

Preparation of different active substances

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
95-63-6	202-436-9	1,2,4-trimethylbenzene	0,1 < 0,3	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Eye Irrit. 2, H319 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Aquatic Chronic 2, H411
64742-48-9	919-857-5	Naphtha (petroleum), hydrotreated heavy	50 < 75	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 3, H412
REACH				
CAS No	Name			REACH registration number
64742-48-9	Naphtha (pet	roleum), hydrotreated heavy		01-2119463258-33

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Call for a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms

Headache

Confusion

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

If swallowed or in the event of vomiting, risk of entering the lungs.

SECTION 5: Firefighting measures

5.1. Extinguishing media Suitable extinguishing media

Alcohol-resistant foam
Dry powder
Carbon dioxide

Water spray jet



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

The product is combustible.

Take precautionary measures against static discharges.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Store in a dry place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
•	Oil Mist	8 hours	5		
		Short-term	10		

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
95-63-6	1,2,4-trimethylbenzene	8 hours	100	20	
DNEL-/PNE	EC-values				
DNEL work	(er				

CAS No	Substance name	Value	Code	Remark
64742-48-9	Naphtha (petroleum), hydrotreated heavy	208 mg/kg bw/day	DNEL long-term dermal (systemic)	
		871 mg/m3	DNEL long-term inhalative (systemic)	

DNEL Consumer

CAS No	Substance name	Value	Code	Remark
64742-48-9	Naphtha (petroleum), hydrotreated heavy	125 mg/kg bw/day	DNEL long-term oral (repeated)	
		125 mg/kg bw/day	DNEL long-term dermal (systemic)	
		185 mg/m3	DNEL long-term inhalative (systemic)	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Filter A or environment-independent breathing apparatus



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min; 60min.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdourliquidyellowishsolvent-like

Odour threshold

Vapour density

not determined					
Important health, safety an	d environmental i	information			
	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling temperature	162 °C				
Melting point / Freezing point	not determined				
Flash point	40 °C				
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	270 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	0,6 Vol-%				
Upper explosion limit	7 Vol-%				
Vapour pressure	1 hPa	20 °C			
Relative density	0,85 g/cm3	20 °C			

not determined



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

	Value	Temperature	at	Method	Remark
Solubility in water					No or low immiscibility
Solubility/other	not determined				
Partition coefficient noctanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	53,1 %				
Solids content	10,7 %				

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No hazardous reactions known.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Thermal decomposition

Remark No decomposition if used as directed.



No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg	rat		CAS: 64742-48-9
LD50 acute dermal	> 5000 mg/kg	rabbit		CAS: 64742-48-9
LC50 acute inhalation	4951 mg/m3 (4 h)	rat		CAS: 64742-48-9
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	non-irritant			
Skin sensitization	non-sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vivo available.
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term

trials.

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

Aspiration hazard

May be fatal if swallowed and enters airways.

Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may caus skin irritation.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Fish	LL/EL/IL50 > 1000 mg/l (96 h)	Oncorhynchus mykiss		CAS: 64742-48-9
Daphnia	EL0 1000 mg/l (48 h)	Daphnia magna		CAS: 64742-48-9



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

	Value	Species	Method	Validation
Algae	NOELR 100 mg/l (72 h)	Pseudokirchneriella		CAS: 64742-48-9
		subcapitata		

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

07 01 04*

other organic solvents, washing liquids and mother liquors

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3295	3295	3295
14.2. UN proper shipping name	HYDROCARBONS, LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated heavy)	HYDROCARBONS, LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated heavy)	Hydrocarbons, liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy)
14.3. Transport hazard class(es)	3	3	3
14.4. Packing group	III	III	III



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.7

W 44 T Multi-Oil

	ADR/RID	IMDG	IATA-DGR
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 3 tunnel restriction code D/E Classification code F1

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 53,1 % **VOC value** 454,1 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.6

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.