

No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product WEICON B Hardener
Code-Nr. 100502

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

Remark

Do not use for private purposes (household).

Recommended intended purpose(s)

2-Component Epoxy Resin - Hardener Component

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255,, DE-48157 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

 Skin Corr. 1C
 H314

 Eye Dam. 1
 H318

 Skin Sens. 1
 H317



No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard **Hazard Statements** Classification procedure categories

Repr. 2

H361f H400 **Aquatic Acute 1 Aquatic Chronic 1** H410

Hazard Statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]









GHS05

GHS07

GHS08

GHS09

Signal word

Danger

Hazard Statements

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H361f Suspected of damaging fertility.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required. P281

P301 + P330 + IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P331

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

P353 water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

P338 easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention. P310 Immediately call a POISON CENTER or doctor/physician. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P391 Collect spillage.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

P405 Store locked up.

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

2-piperazin-1-ylethylamine, 4,4'-isopropylidenediphenol, Fatty acids C18 unsat, reaction products with tetraethylenepentamine

Additional information

Remark

For industrial use only.

2.3. Other hazards

Information pertaining to special dangers for human and environment

Causes severe burns.

Possible risk of impaired fertility.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Polyamino amide.

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
80-05-7	201-245-8	4,4`-lsopropylidendiphenol	7 - 13	Eye Dam. 1, H318 / Skin Sens. 1, H317 / Repr. 2, H361f / STOT SE 3, H335 / Aquatic Chronic 2, H411
140-31-8	205-411-0	2-piperazin-1-ylethylamine	3 - 7	Acute Tox. 4, H302 / Acute Tox. 3, H311 / Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412
1226892-45-0	273-201-6	Fatty acids C18 unsat, reaction products with tetraethylenepentamine	60 - 99,9	Skin Corr. 1C, H314 / Eye Dam. 1, H318 / Skin Sens. 1A, H317 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410

REACH

CAS No	Name	REACH registration number
80-05-7	4,4`-lsopropylidendiphenol	01-2119457856-23
140-31-8	2-piperazin-1-ylethylamine	01-2119471486-30
1226892-45-0	Fatty acids C18 unsat, reaction products with tetraethylenepentamine	01-2119487006-38

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

No mouth-to-mouth resuscitation by first aid.

Seek medical advice immediately.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

In case of skin contact

In case of contact with skin wash off immediately with plenty of water.

Immediate medical treatment necessary, as untreated burns can result in slow-healing wounds.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

Do not induce vomiting

Call for a doctor immediately.

Rinse out mouth thoroughly with water.

4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms

vomiting

Respiratory complaints

Headache

Allergic symptoms

Skin burns

Nausea

Confusion

Gastrointestinal complaints

Physician's information / possible dangers

Risk of respiratory disorders

allergic reactions

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

Keep under medical supervision for at least 48 hours.

Symptoms may not occur until several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not seep away runed out product into ground or body of water.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

Take the usual precautions when handling with chemicals.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

It is essential for pregnant women to avoid inhaling the product and not to let it come in contact with the skin.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store with acids or alkalies.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

Store at 5 to 40°C (=41 to 104°F).

Store in a dry place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Selection of the appropriate filter type depends on the quantity and chemicals handled at the workplace. Contact supplier of respiratory protective equipment or more information about filter properties.

Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Butyl rubber; 0,7 mm; 480min; 60min. "Butoject 898" from KCL; Email: Vertrieb@kcl.de

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles protective shield

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colour Odour

liquid blue hardly noticeable

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	11	20 °C			1:1 in water
boiling point	> 200 °C				
melting point	not determine	ed			



No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

	Value	Temperature	at	Method	Remark
Flash point	147 °C			DIN 51758	Pensky-Martens Closed Cup
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	not determined				
Self ignition temperature	not applicable				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	10 Pa	20 °C			
Relative density	0,98 g/cm3	25 °C			
Vapour density	not determined				
Solubility in water		20 °C			insoluble
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	> 200 °C				
Viscosity dynamic	450-900 mPa*s	25 °C			
Viscosity kinematic	not determined	40 °C			
Oxidising properties No information available.					
Explosive properties not determined					
9.2. Other information No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.



No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies. Reactions with strong oxidising agents.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials Substances to avoid

Alkali (lye), concentrated Acid, concentrated Oxidising agent, strong

10.6. Hazardous decomposition products

Gases/vapours, toxic Carbon monoxide and carbon dioxide. Nitrous oxides (NOx)

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	4100 mg/kg	rat		Calculated out of the components.
LD50 acute dermal	866 mg/kg	rabbit		CAS: 140-31-8
LC50 acute inhalation	> 170 mg/m3 (6 h)	rat		CAS: 80-05-7
Skin irritation	corrosive	rabbit	OECD 404	
Eye irritation	corrosive	rabbit eye	OECD 405	
Skin sensitization	sensitizing	Guinea pig	OECD 406	
Subacute Toxicity - C	Carcinogenicity			
	Value	Species	Method	Validation
Chronic Toxicity	NOAEL > 300 mg/kg OECD 422			-
Mutagenicity				No mutagenity, after different in-vitro studies.
Reproduction- Toxicity	NOEL 5 mg/kg	Rat	OECD 416	Indications of toxic effects are available from reproduction studies in animals.
	Experimental value			

CAS: 140-31-8



trials

No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

Value Method Validation **Species** No indications of carcinogenic Carcinogenicity effects are available from long-term

Specific target organ toxicity (single exposure)

not applicable

Toxicity test (Additional information)

Indications of genotoxic effects at humans are available from reproduction studies in animals.

Experiences made from practice

Risk of strong health injuries in case of long-term exposition.

Corrosive effect on skin and mucous membrane.

Sensitization through skin contact possible.

Causes corrosions.

Risk of strong eye injuries.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

3	Value	Species	Method	Validation
Fish	LC50 0,19 mg/l (96 h)	Fish	OECD 203	CAS: 1226892-45-0
Daphnia	EC 50 0,18 mg/l (48 h)	Daphnia sp.	OECD 202	CAS: 1226892-45-0
Algae	EC50 > 1000 mg/l (72 h)	Green algae	OECD 201	CAS: 140-31-8
Bacteria	EC0 109,4 mg/l (3 h)	activated sludge	OECD 209	CAS: 1226892-45-0
12.2. Persister	nce and degradability Elimination rate	Method of analysis	Method	Validation
Biological	89 % (48 d)		OECD 303A	Biodegradable
degradability	CAS: 1226892-45-0			
Degradability	0 % (28 d)		OECD 301 F	not readily degradable
	CAS: 140-31-8			

12.3. Bioaccumulative potential

Slight bioaccumulation potential.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Very toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

07 02 04*

other organic solvents, washing liquids and mother liquors

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Empty containers can be deposited after cleaning in accordance with the local waste regulations.

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	2735	2735	2735
14.2. UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. (Polyamidoimidazoline, Tetraethylenpentamin)	AMINES, LIQUID, CORROSIVE, N.O.S. ((TETRAETHYLENE PENTAMINE) (AMINOETHYLPIPERAZINE))	Amines, liquid, corrosive, n.o. s. ((TETRAETHYLENE PENTAMINE) (AMINOETHYLPIPERAZINE))
14.3. Transport hazard class(es)	8	8	8
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 8 tunnel restriction code E Classification code C7

Marine transport IMDG

MARINE POLLUTANT



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

WEICON B Hardener

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H361f	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.