

No. 1907/2006 (REACH)
Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product WEICON C Hardener Code-Nr. 101002

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Hardener Component

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster Postbox 48045, DE-8460 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

Emergency advice -

Phone -

GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)

Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard Hazard Statements Classification procedure categories

Acute Tox. 4 H302

 Acute Tox. 4
 H302

 Skin Corr. 1B
 H314

 Eye Dam. 1
 H318

 Skin Sens. 1
 H317



No. 1907/2006 (REACH)
Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements

Classification procedure

categories

Aquatic Chronic 3 H412

Hazard Statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS05

GHS07

Signal word

Danger

Hazard Statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

P102 Keep out of reach of children.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do no eat, drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301 + P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P301 + P330 + IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P331

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

P353 water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

P338 easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P330 Rinse mouth.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container to hazardous or special waste collection point.



No. 1907/2006 (REACH)
Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

Hazardous ingredients for labeling

1-methylimidazole, 3-Aminomethyl-3,5, 5-trimethylcyclohexylamin, M-phenylenebis (methylamine)

2.3. Other hazards

Information pertaining to special dangers for human and environment

Causes severe burns.

Risk of serious damage to eyes.

Danger of serious damage to health by prolonged exposure.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Aliphatic and cyclo-aliphatic polyamine.

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
2855-13-2	220-666-8	3-Aminomethyl-3,5, 5- trimethylcyclohexylamin	13 - 30	Acute Tox. 4, H302, H312 / Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412
1477-55-0	216-032-5	M-phenylenebis (methylamine)	13 - 30	Acute Tox. 4, H302, H332 / Skin Corr. 1B, H314 / Eye Dam. 1, H318 / Skin Sens. 1, H317 / Aquatic Chronic 3, H412
616-47-7	210-484-7	1-methylimidazole	3 - 7	Acute Tox. 4, H302 / Acute Tox. 3, H311 / Skin Corr. 1B, H314 / Eye Dam. 1, H318

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In case of inhalation of fumes symptoms of poisoning may occur after hours, medical treatment is necessary. Seek medical treatment immediately.

In case of skin contact

In case of contact with skin wash off with soap and water.

Remove contaminated clothing immediately, even underwear and shoes.

Seek medical treatment immediately.

In case of eye contact

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Call for a doctor immediately.

Give water to drink in small sips.

Rinse out mouth thoroughly with water.



No. 1907/2006 (REACH)
Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms

Stomache -ache

vomiting

Respiratory complaints

Headache

Allergic symptoms

Skin burns

Nausea

Gastrointestinal complaints

Physician's information / possible dangers

allergic reactions

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

If swallowed or in the event of vomiting, risk of entering the lungs.

Keep under medical supervision for at least 48 hours.

Symptoms may not occur until several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.



No. 1907/2006 (REACH)
Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust). After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Wash hands and skin before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

Storage temperature between 2°C to 40°C

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.



No. 1907/2006 (REACH) Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles protective shield

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colour Odour

liquid light yellow hardly noticeable

Odour threshold not determined

Solubility in water

Important health, safety and environmental information					
	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	> 200 °C				
Melting point / Freezing point	not determined				
Flash point	106 °C			DIN 51758	Pensky-Martens Closed Cup
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	< 0,002 kPa	20 °C			
Relative density	1,01 g/cm3	25 °C			
Vapour density	not determined				

20 °C

more or less insoluble



No. 1907/2006 (REACH)
Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

	Value	Temperature	at	Method	Remark
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	> 200 °C				
Viscosity dynamic	800 - 16000 mPa*s	25 °C			
Viscosity kinematic	not determined	40 °C			
Oxidising properties No information available.					
Explosive properties No information available.					
9.2. Other information No information available.					

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

Reactions with strong acids and alkalies. Reactions with strong oxidising agents.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials Substances to avoid

Alkali (lye), concentrated Acid, concentrated Oxidising agent, strong

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx) Toxic gases/vapours

Thermal decomposition

Remark No decomposition if used as directed.



No. 1907/2006 (REACH)
Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

! SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	1929,2 mg/kg			ATE
LD50 acute dermal	2284,5 mg/kg			ATE
LC50 acute inhalation	7,839 mg/l ()			ATE
Skin irritation	corrosive	rabbit		
Eye irritation	corrosive	rabbit eye		
Skin sensitization	sensitizing	Guinea pig		

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Chronic Toxicity	NOAEL 30 mg/kg (90 d) Repeated Dose 90-Day (OECD 422	Oral Toxicity Study in Rodents	CAS: 616-47-7	-
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-	NOEL 150 ma/ka	Rat	OECD 421	

Experiences made from practice

Risk of strong health injuries in case of long-term exposition.

Corrosive effect on skin and mucous membrane.

Sensitization through skin contact possible.

Causes corrosions.

Toxicity

Risk of strong eye injuries.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Fish	LC50 100 - 215 mg/l (96 h)	Fish	DIN 38412 T.15	CAS: 616-47-7
Daphnia	EC50 15,2 mg/l (48 h)	Daphnia sp.	OECD 202	CAS: 1477-55-0
Algae	ErC50 180,7 mg/l (72 h)	Green algae	OECD 201	CAS: 616-47-7
Bacteria	EC50 1050 mg/l (17 h)	No data available	DIN 38412 T.8	CAS: 616-47-7



No. 1907/2006 (REACH)
Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

12.2. Persistence a	and degradability Elimination rate	Method of analysis	Method	Validation
Biological	0 - 10 % (28 d)		OECD 301 F	not readily degradable
degradability	CAS: 616-47-7			

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

! SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

07 02 04*

other organic solvents, washing liquids and mother liquors

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

! Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

! SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	2735	2735	2735
14.2. UN proper shipping name	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Metaxylenediamine)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Metaxylenediamine)	Polyamines, liquid, corrosive, n.o.s. (Metaxylenediamine)
14.3. Transport hazard class(es)	8	8	8
14.4. Packing group	II	II	II



No. 1907/2006 (REACH)
Printed 07.01.2016

revision 05.01.2016 (GB) Version 8.4

WEICON C Hardener

	ADR/RID	IMDG	IATA-DGR
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 8 tunnel restriction code E Special provisions 274 Classification code C7

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 0 %

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

H302	Harmful if swallowed.
H302,	-?-
H302,	-?-
H332	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H412	Harmful to aquatic life with long lasting effects.