

**WEICON F Resin****! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** WEICON F Resin  
Code-Nr. 101501

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended intended purpose(s)**

2-Component Epoxy Resin - Resin Component

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255,, DE-48157 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone ++49(0)251 / 9322 - 0  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
Skin Sens. 1	H317	
Aquatic Chronic 2	H411	

**Hazard Statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

**2.2. Label elements**

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07



GHS09

**Signal word**

Warning

**Hazard Statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary Statements**

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P501	Dispose of contents/container to hazardous or special waste collection point.

**Hazardous ingredients for labeling**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight &lt;= 700)

**Special rules for supplemental label elements for certain mixtures**

Contains epoxy constituents. May produce an allergic reaction.

**2.3. Other hazards****Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures****Description**

Formulated Bisphenol-A-Epoxy Resin.



# Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Printed 02.09.2016  
revision 03.08.2016 (GB) Version 8.4

## WEICON F Resin

### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	30 - 60	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
38640-62-9	254-052-6	Bis(isopropyl)naphthalene	7 - 13	Asp. Tox. 1, H304 / Aquatic Chronic 1, H410

### REACH

CAS No	Name	REACH registration number
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26-xxxx

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

#### In case of eye contact

In case of contact with eyes rinse thoroughly with warm water.

Call for a doctor immediately.

#### In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Call for a doctor immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

#### Physician's information / possible symptoms

vomiting

Respiratory complaints

Allergic symptoms

Nausea

skin irritation

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Treatment (Advice to doctor)

Keep under medical supervision for at least 48 hours.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Product does not burn, fire-extinguishing activities according to surrounding.



---

## 5.2. Special hazards arising from the substance or mixture

Metal oxides

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

## 5.3. Advice for firefighters

### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

### Additional information

Collect contaminated firefighting water separately, must not be discharged into the drains.

---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

### 6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

#### General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

#### Hygiene measures

At work do not eat, drink and smoke.

Remove soaked clothing immediately.

Wash hands before breaks and after work.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Pay attention to general rules of internal fire prevention.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

**Advice on storage compatibility**

Do not store with acids or alkalis.

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

**Further information on storage conditions**

Keep container tightly closed and store at cool and aired place.

Keep container tightly closed, open and handle carefully.

Protect from frost.

Protect from heat and direct solar radiation.

Storage temperature between 2°C to 40°C

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
		8,33 mg/kg bw/day	DNEL long-term dermal (local)	
		12,25 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	
38640-62-9	Bis(isopropyl)naphthalene	4,3 mg/kg bw/day	DNEL long-term dermal (systemic)	
		30 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	

**PNEC**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	0,996 mg/kg	PNEC sediment, freshwater	
		10 mg/l	PNEC sewage treatment plant (STP)	
		0,0006 mg/l	PNEC aquatic, marine water	
		0,006 mg/l	PNEC aquatic, freshwater	
		0,0996 mg/kg	PNEC sediment, marine water	
38640-62-9	Bis(isopropyl)naphthalene	0,15 mg/l	PNEC sewage treatment plant (STP)	
		0,26 µg/l	PNEC aquatic, freshwater	
		0,094 mg/kg	PNEC sediment, marine water	
		0,94 mg/kg	PNEC sediment, freshwater	



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

## WEICON F Resin

### DNEL-/PNEC-values (continued)

CAS No	Substance name	Value	Code	Remark
		0,026 µg/l	PNEC aquatic, marine water	

### Additional advice

The statutory local and national regulations have to be observed.

### 8.2. Exposure controls

#### Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

#### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

#### Eye protection

tightly fitting goggles

#### Other protection measures

protective clothing

#### Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Colour	Odour
pasty	grey	hardly noticeable

#### Odour threshold

not determined

#### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not determined				
<b>boiling point</b>	> 200 °C				
<b>melting point</b>	not determined				
<b>Flash point</b>	> 200 °C			DIN 51758	Pensky-Martens Closed Cup
<b>Vapourisation rate</b>	not determined				
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not determined				
<b>Ignition temperature</b>	not applicable				

**WEICON F Resin**

	Value	Temperature	at	Method	Remark
<b>Self ignition temperature</b>	not determined				
<b>Lower explosion limit</b>	not determined				
<b>Upper explosion limit</b>	not determined				
<b>Vapour pressure</b>	< 0,01 Pa	20 °C			
<b>Relative density</b>	2,1 g/cm <sup>3</sup>	25 °C			
<b>Vapour density</b>	not determined				
<b>Solubility in water</b>		20 °C			insoluble
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	> 200 °C				
<b>Viscosity dynamic</b>	not determined				
<b>Viscosity kinematic</b>	not determined	40 °C			
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	not applicable				
<b>9.2. Other information</b>	No information available.				

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

Reactions with strong acids and alkalis.

Reactions with strong oxidising agents.

**10.4. Conditions to avoid**

Keep away from heat.

**10.5. Incompatible materials****Substances to avoid**

Alkali (lye), concentrated

Acid, concentrated

Oxidising agent, strong

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

Toxic gases/vapours

**Thermal decomposition**

Remark No decomposition if used as directed.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	> 2000 mg/kg	rat		CAS: 25068-38-6
<b>LD50 acute dermal</b>	> 2000 mg/kg	rat		CAS: 25068-38-6
<b>LC50 acute inhalation</b>	1E-5 ppm (5 h)	rat		CAS: 25068-38-6
<b>Skin irritation</b>	irritant	rabbit	OECD 404	
<b>Eye irritation</b>	irritant	rabbit eye	OECD 405	
<b>Skin sensitization</b>	sensitizing		OECD 429	

**Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
<b>Chronic Toxicity</b>	NOAEL 50 mg/kg (90 d) Repeated Dose 90-Day Oral Toxicity Study in Rodents OECD 408			-
<b>Mutagenicity</b>				No experimental information on genotoxicity in vitro available.
<b>Reproduction-Toxicity</b>	NOEL 540 mg/kg	Rat	OECD 416	No indications of toxic effects were observed in reproduction studies in animals.
<b>Carcinogenicity</b>				No indications of carcinogenic effects are available from long-term trials.

**Experiences made from practice**

Sensitization through skin contact possible.

Irritates eyes and skin.

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.



**SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
<b>Fish</b>	LC50 1,5 mg/l (96 h)	Fish	OECD 203	CAS: 25068-38-6
<b>Daphnia</b>	EC 50 1,7 mg/l (48 h)	Daphnia sp.	OECD 202	CAS: 25068-38-6
<b>Algae</b>	EC50 9,4 mg/l (72 h)	Green algae	EPA CFR	CAS: 25068-38-6
<b>Bacteria</b>	IC50 > 100 mg/l (3 h)	activated sludge		CAS: 25068-38-6

**12.2. Persistence and degradability**

	Elimination rate	Method of analysis	Method	Validation
<b>Biological degradability</b>	5 % (28 d) CAS: 25068-38-6		OECD 301 F	not readily degradable

**12.3. Bioaccumulative potential**

Slight bioaccumulation potential.

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****General regulation**

Toxic to aquatic life with long lasting effects.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Waste code No.**

07 02 08\*

**Name of waste**

other still bottoms and reaction residues

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

**Recommendations for packaging**

Empty containers can be deposited after cleaning in accordance with the local waste regulations.

**General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	<b>ADR/RID</b>	<b>IMDG</b>	<b>IATA-DGR</b>
<b>14.1. UN number</b>	3082	3082	3082
<b>14.2. UN proper shipping name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (BISPHENOL A EPOXY HARZ)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)	Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN)
<b>14.3. Transport hazard class(es)</b>	9	9	9
<b>14.4. Packing group</b>	III	III	III
<b>14.5. Environmental hazards</b>	Yes	Yes	Yes

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**Land and inland navigation transport ADR/RID**

Hazard label(s) 9

tunnel restriction code E

Special provisions 274 335 601

Classification code M6

**Marine transport IMDG**

MARINE POLLUTANT

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard****VOC content** 0 %**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

H304 May be fatal if swallowed and enters airways.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

**WEICON F Resin**

---

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.