

No. 1907/2006 (REACH) Printed 08.01.2016

revision 03.09.2014 (GB) Version 8.1

Urethane Hardener 60

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Urethane Hardener 60 Code-Nr. 105103

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Hardener Component

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

> Königsberger Str. 255, DE-48157 Münster Postbox 48045, DE-8460 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

> Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

Emergency advice

Phone

GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)

Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

! SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories

Hazard Statements Classification procedure

Skin Sens. 1 H317 **Aquatic Chronic 2** H411

Hazard Statements

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.



No. 1907/2006 (REACH)
Printed 08.01.2016

revision 03.09.2014 (GB) Version 8.1

Urethane Hardener 60

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS07

GHS09

! Signal word

Warning

Hazard Statements

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P261 P272 P273 P280	Avoid breathing dust/fume/gas/mist/vapours/spray. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 P333 + P313 P363 P391	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Collect spillage.
P501	Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine

! Special rules for supplemental label elements for certain mixtures

Contains 6-Methyl-2,4-bis(methylthio)phenylene-1,3-diamine. May cause allergic reactions.

2.3. Other hazards

! Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

! Description

aromatic diamine compound

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
106264-79-3	403-240-8	6-methyl-2,4-bis(methylthio)phenylene-1, 3-diamine	10 < 25	Acute Tox. 4, H302 / Skin Sens. 1, H317 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
27236-65-3	234-835-5	Diphenyl[µ[(tetrapropenyl)succinato(2-)- O:O´]] diquecksilber	0,1 < 0,25	Acute Tox. 3, H301 / STOT RE 1, H372 / Skin Corr. 1B, H314 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410



No. 1907/2006 (REACH)
Printed 08.01.2016

revision 03.09.2014 (GB) Version 8.1

Urethane Hardener 60

! SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

! In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

! In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

Rinse out mouth and give plenty of water to drink.

4.2. Most important symptoms and effects, both acute and delayed

! Physician's information / possible symptoms

Allergic symptoms

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

! SECTION 5: Firefighting measures

5.1. Extinguishing media

! Suitable extinguishing media

Alcohol-resistant foam

Dry fire-extinguishing substance

Carbon dioxide

Unsuitable extinguishing media

water

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Ammonia

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

5.3. Advice for firefighters

! Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

! Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.



No. 1907/2006 (REACH)
Printed 08.01.2016

revision 03.09.2014 (GB) Version 8.1

Urethane Hardener 60

! SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

! For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

! Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

! Advice on storage compatibility

Do not store with acids or alkalies.

Do not store with oxidizing agents.

Do not store together with animal feedstuffs.

Do not store together with food.

Keep away from water.

! Further information on storage conditions

Keep container tightly closed.

Store only in original container at cool and aired place.

Protect from atmospheric moisture and water

Store in a dry place.



No. 1907/2006 (REACH)
Printed 08.01.2016

revision 03.09.2014 (GB) Version 8.1

Urethane Hardener 60

7.3. Specific end use(s)

! Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min; 60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

! Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

! SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colour Odour

liquid brown similar to amine

Odour threshold not determined

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark	
pH value	not determined					_
boiling point	> 200 °C			DIN 53171		
melting point	not determined					
Flash point	> 150 °C			closed cup		
Vapourisation rate	not determined					
Flammable (solid)	not determined					
Flammability (gas)	not determined					



No. 1907/2006 (REACH)
Printed 08.01.2016

revision 03.09.2014 (GB) Version 8.1

Urethane Hardener 60

	Value	Temperature	at	Method	Remark
Ignition temperature	340 °C			DIN 51794	
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	0,3 Vol-%				
Upper explosion limit	2,8 Vol-%				
Vapour pressure	not determined				
Relative density	1 g/cm3	20 °C		ISO 2811	
Vapour density	not determined				
Solubility in water					No or low immiscibility
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	380 mPa*s	25 °C		ISO 9371	
Oxidising properties					

No information available.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

9.2. Other information

No information available.

! SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

Reactions with acids, alkalies and oxidising agents.

Exothermic reaction with hardener component.

Reactions with water.

Violent reactions with concentrated alkalies and oxidising agents.

10.4. Conditions to avoid

Water

10.5. Incompatible materials

! Substances to avoid

Alkali (lye), concentrated Acid, concentrated Oxidising agent, strong



No. 1907/2006 (REACH)
Printed 08.01.2016

revision 03.09.2014 (GB) Version 8.1

Urethane Hardener 60

Water

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx)

Ammonia

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark	
Skin irritation	non-irritant				
Eye irritation	non-irritant				

Experiences made from practice

Sensitization through skin contact possible.

! Additional information

Skin sensitization

The product is to be handled with the caution usual with chemicals.

sensitizing

Other hazardous properties may not be excluded.

! SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

! General regulation

Toxic to aquatic life, fishes and plankton.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Toxic to fishes.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.



No. 1907/2006 (REACH)
Printed 08.01.2016

revision 03.09.2014 (GB) Version 8.1

Urethane Hardener 60

! SECTION 13: Disposal considerations

13.1. Waste treatment methods

! Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

Recommendations for packaging

Dispose of according to the local waste regulations.

! SECTION 14: Transport information

•	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3082	3082	3082
14.2. UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N. O.S. (6-methyl-2,4-bis(methylthio)phenylene- 1,3-diamine)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (6-methyl-2,4- bis(methylthio)phenylene-1,3- diamine)	Environmentally hazardous substance, liquid, n.o.s. (6-methyl-2,4-bis(methylthio) phenylene-1,3-diamine)
14.3. Transport hazard class(es)	9	9	9
14.4. Packing group	III	III	III
14.5. Environmental hazards	s No	No	No

14.6. Special precautions for user

Caution: Dangerous substances and objects.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 9 tunnel restriction code E Classification code M6

Marine transport IMDG

MARINE POLLUTANT

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

 $\begin{array}{lll} \textbf{VOC content} & 0.2 \ \% \\ \textbf{VOC value} & 2 \ g/L \end{array}$

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



No. 1907/2006 (REACH)
Printed 08.01.2016

revision 03.09.2014 (GB) Version 8.1

Urethane Hardener 60

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.0

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H372	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.