

No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Rust Loosener and Contact Spray

Code-Nr. 111500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255,, DE-48157 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Aerosol 1 H222, H229 Aquatic Chronic 2 H411

Hazard Statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS02

GHS09

Signal word

Danger

Hazard Statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3. Other hazards

P501

Product has an anesthetic effect.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Mixture of active ingredients with propellant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
74-98-6	200-827-9	propane	10 < 25	Flam. Gas 1, H220 / Press. Gas
	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	10 < 25	Asp. Tox. 1, H304



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
110-25-8	203-749-3	(Z)-N-methyl-N-(1-oxo-9-octadecenyl) glycine	0,1 < 1	Eye Dam. 1, H318 / Aquatic Acute 1, H400 / Acute Tox. 4, H332 / Skin Irrit. 2, H315
95-38-5	202-414-9	2-(2-Heptadec-8-enyl-2-imidazolin-1-yl) ethanol	0,1 < 1	Acute Tox. 4, H302 / Skin Corr. 1C, H314 / Aquatic Acute 1, H400 M=1 / Aquatic Chronic 1, H410 M=10 /
REACH				
CAS No	Name			REACH registration number
74-98-6	propane			01-2119486944-21
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics			01-2119457273-39-xxxx
110-25-8	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine			01-2119488991-20
95-38-5	2-(2-Hentade	ec-8-enyl-2-imidazolin-1-yl)ethanol		01-2119777867-13

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

water mist

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Keep people away and stay on the upwind side.

Use personal protective clothing.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale aerosols

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

Avoid effect of heat.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
•	Oil Mist	8 hours	5		
		Short-term	10		

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min:60min

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.



No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdouraerosolcolourlesscharacteristic

Odour threshold not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
melting point	not applicable				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not determined				
Ignition temperature	236 °C				
Self ignition temperature					no
Lower explosion limit	0,7 Vol-%				
Upper explosion limit	10,9 Vol-%				
Vapour pressure	8300 hPa	20 °C			
Relative density	0,803 g/cm3	20 °C			
Vapour density	not determined				
Solubility in water					No or low immiscibility
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	25,2 %				
Solids content	0,3 %				



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

Formation of inflammable vapour-air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg	rat		EG: 918-481-9
LD50 acute dermal	> 5000 mg/kg	rabbit		EG: 918-481-9
LC50 acute inhalation	> 4951 mg/l (4 h)	rat		EG: 918-481-9
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

Subacute Toxicity - Carcinogenicity				
	Value	Species	Method	Validation
Chronic Toxicity				-
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

	Value	Species	Method	Validation
Fish	LL0 1000 mg/l (96 h)	Oncorhynchus mykiss		EG: 918-481-9
Daphnia	EL0 1000 mg/l (48 h)	Daphnia magna		EG: 918-481-9
Algae	EL0 1000 mg/l (72 h)	Pseudokirchneriella subcapitata		EG: 918-481-9

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Harmful to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

Harmfull to fishes and bacteria.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

15 01 10*

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1 tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

 VOC content
 25,2 %

 VOC value
 202 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Rust Loosener and Contact Spray

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Danish MAL Code 5-3

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

H220	Extremely flammable gas.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.