



Rust Shock Spray

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Rust Shock Spray
Code-Nr. 111510

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255,, DE-48157 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone ++49(0)251 / 9322 - 0
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories Hazard Statements Classification procedure

Aerosol 1 H222, H229
Eye Dam. 1 H318

Hazard Statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H318 Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]


GHS02



GHS05

Signal word

Danger

Hazard Statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H318 Causes serious eye damage.

Precautionary Statements

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER or doctor/physician.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

propan-1-ol

2.3. Other hazards

Caution! Container under pressure.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients
3.1. Substances

not applicable

3.2. Mixtures
Description

Propellant: propane / butane

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
64-17-5	200-578-6	ethanol	50 - 70	Flam. Liq. 2, H225
71-23-8	200-746-9	propan-1-ol	10 < 20	Flam. Liq. 2, H225 / Eye Dam. 1, H318 / STOT SE 3, H336



Safety Data Sheet according to Regulation (EC)
No. 1907/2006 (REACH)

Printed 02.09.2016
revision 03.08.2016 (GB) Version 8.5

Rust Shock Spray

Hazardous ingredients (continued)

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
74-98-6	200-827-9	propane	1 - 10	Flam. Gas 1, H220 / Press. Gas
75-28-5	200-857-2	isobutane	1 - 10	Flam. Gas 1, H220 / Press. Gas
106-97-8	203-448-7	butane	10 - 20	Flam. Gas 1, H220 / Press. Gas

Labelling for contents according to regulation (EC) No 648/2004, annex VII

15 % or over but less than 30 % aliphatic hydrocarbons

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

May lead to formation of explosive/easily ignitable vapour air mixtures.

Danger of bursting

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up residues with absorbent material (e.g. sand, sawdust, general-purpose binder).

After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.

Informations for disposal see chapter 13.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale gases/vapours/aerosols.

Avoid contact with the eyes.

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Protect from heat and sunlight.

The product is combustible.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from heat and direct solar radiation.

Keep container in a well-ventilated place

Storage temperature may not exceed 50°C (=122°F).

Keep in a cool place.

**Rust Shock Spray****7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
64-17-5	ethanol	8 hours	1920	1000	EH40/2005

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
64-17-5	ethanol	1900 mg/m3	DNEL acute inhalative (local)	
		950 mg/m3	DNEL acute inhalative (systemic)	
		343 mg/kg	DNEL long-term dermal (systemic)	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Hand protection

Glove material specification: Butyl rubber

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

aerosol

Colour

colourless

Odour

alcoholic

Odour threshold

**Rust Shock Spray**

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not applicable				
boiling point	not applicable				
melting point	No data available				
Flash point	-60 °C				
Vapourisation rate	not applicable				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	360 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	1,5 Vol-%				
Upper explosion limit	15 Vol-%				
Vapour pressure	2700 hPa	20 °C			
Relative density	0,71 g/cm ³	20 °C			
Vapour density	not determined				
Solubility in water					miscible
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.



SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

no

10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
Skin irritation	No stimulation effect.			
Eye irritation	irritant - risk of strong eye injuries			
Skin sensitization	non-sensitizing			

Experiences made from practice

Inhalation causes narcotic effect/intoxication.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

**Rust Shock Spray**

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste code No.**

15 01 04

15 01 10*

Name of waste

metallic packaging

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommended cleansing agent

Water

General information

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 96,25 %

VOC value 682 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.