

No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Alu-Grinding Protection

Code-Nr. 114510

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255,, DE-48157 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Aerosol 1 H222, H229
STOT SE 3 H336
Aquatic Chronic 2 H411

Hazard Statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]







GHS02

GHS07

GHS09

Signal word

Danger

Hazard Statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

| P102 | Keep out of reach of children. |
|------|--------------------------------|
|------|--------------------------------|

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

pentane

2.3. Other hazards

Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Mixture of active ingredients with propellant

Hazardous ingredients

| CAS No | EC No | Name | [% weight] | Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] |
|----------|-----------|--------|---------------|---|
| 106-97-8 | 203-448-7 | butane | 10 - 25 | Flam. Gas 1, H220 / Press. Gas |



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

| CAS No | EC No | Name | [% weight] | Classification according to Regulation (EC) No 1272/2008 [CLP/GHS] |
|----------|-----------|---------|---------------|--|
| 109-66-0 | 203-692-4 | pentane | 50 - 75 | Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411 |
| 74-98-6 | 200-827-9 | propane | 10 - 25 | Flam. Gas 1, H220 / Press. Gas |
| REACH | | | | |
| CAS No | Name | | | REACH registration number |
| 74-98-6 | propane | | | 01-2119486944-21 |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms

Anaesthetic state

Headache

Confusion

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Protect from heat and sunlight.

Vapours can form an explosive mixture with air.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Keep in a cool place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

| CAS No | Name | Code | [mg/m3] | [ppm] | Remark |
|----------|--------|------------|---------|-------|-----------|
| 106-97-8 | Butane | 8 hours | 1450 | 600 | EH40/2005 |
| | | Short-term | 1810 | 750 | |

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

| CAS No | Name | Code | [mg/m3] | [ppm] | Remark |
|----------|---------|---------|---------|-------|--------|
| 109-66-0 | pentane | 8 hours | 3000 | 1000 | |

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Short-term: filter apparatus, filter AX/P2, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.



No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdouraerosolcolourless, clearcharacteristic

Odour threshold not determined

Important health, safety and environmental information

| | Value | Temperature | at | Method | Remark |
|---|----------------|-------------|----|--------|-----------------------------------|
| pH value | not determined | | | | |
| boiling point | -44 °C | | | | |
| melting point | not determined | | | | |
| Flash point | not applicable | | | | Aerosol |
| Vapourisation rate | not applicable | | | | |
| Flammable (solid) | not applicable | | | | |
| Flammability (gas) | not applicable | | | | |
| Ignition temperature | 285 °C | | | | |
| Self ignition temperature | | | | | The product is not self-igniting. |
| Lower explosion limit | 1,4 Vol-% | | | | |
| Upper explosion limit | 10,9 Vol-% | | | | |
| Vapour pressure | 8300 hPa | | | | |
| Relative density | ca. 0,61 g/ml | 20 °C | | | |
| Vapour density | not determined | | | | |
| Solubility in water | | | | | No or low immiscibility |
| Solubility/other | not determined | | | | |
| Partition coefficient n- octanol/water (log P O/W) | not determined | | | | |
| Decomposition temperature | not determined | | | | |
| Viscosity dynamic | not determined | | | | |
| Viscosity kinematic | not determined | | | | |
| Solvent content | ca. 94 % | | | | |
| Solids content | ca. 6 % | | | | |
| | | | | | |



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

9.2. Other information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

| | Value/Validation | Species | Method | Remark |
|-----------------|------------------|---------|--------|--------|
| Skin irritation | non-irritant | | | |
| Eye irritation | non-irritant | | | |

Additional information

Skin sensitization

The product is to be handled with the caution usual with chemicals.

non-sensitizing

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from products of similar composition.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicological effects

| LCOTOXICOTOS | Value | Species | Method | Validation | |
|--------------|-----------------------|---------------------------------|--------|---------------|--|
| Fish | LC50 4,26 mg/l (96 h) | Oncorhynchus myk | iss | CAS: 109-66-0 | |
| Daphnia | EC50 2,7 mg/l (48 h) | Daphnia magna | | CAS: 109-66-0 | |
| Algae | NOEC 7,51 mg/l (72 h) | Pseudokirchneriella subcapitata | ı | CAS: 109-66-0 | |

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Other adverse effects

General regulation

Toxic to aquatic life with long lasting effects.

Toxic to fishes.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

metallic packaging

07 01 04*

other organic solvents, washing liquids and mother liquors

15 01 04

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

SECTION 14: Transport information

| | ADR/RID | IMDG | IATA-DGR |
|-----------------|---------|------|----------|
| 14.1. UN number | 1950 | 1950 | 1950 |



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

| | | ADR/RID | IMDG | IATA-DGR |
|----------------|---------------------------|--------------------|--------------------|-------------------------------|
| 14.2. name | UN proper shipping e | AEROSOLS (pentane) | AEROSOLS (pentane) | Aerosols, flammable (pentane) |
| 14.3. class | Transport hazard s(es) | 2.1 | 2.1 | 2.1 |
| 14.4. | Packing group | - | - | - |
| 14.5. | Environmental hazards | Yes | Yes | Yes |

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1 tunnel restriction code D Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

MARINE POLLUTANT

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 94 % **VOC value** 569,6 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

Sources of key data used

Danish MAL Code 2-1 VOC-CH 94,00%

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.



No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.5

Alu-Grinding Protection

H411 Toxic to aquatic life with long lasting effects.