



! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Spray on Grease with MoS2
Code-Nr. 115300

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Distributor

WEICON GmbH & Co. KG
Königsberger Str. 255,, DE-48157 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department
Phone ++49(0)251 / 9322 - 0
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229	
-----------	------------	--

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]


GHS02

Signal word

Danger

Hazard Statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.

Precautionary Statements

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P271 Use only outdoors or in a well-ventilated area.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards
Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/ information on ingredients
3.1. Substances

not applicable

3.2. Mixtures
Description

Preparation of metallic soap in mineral oil oil with additives

Mixture of active ingredients with propellant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-63-0	200-661-7	propan-2-ol	< 10	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
61641-74-5		propane/butane-mixture	40 - 50	Flam. Gas 1, H220 / Press Gas, H280

REACH

CAS No	Name	REACH registration number
67-63-0	propan-2-ol	01-2119457558-25



SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Dry powder

Carbon dioxide

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Danger of bursting

In case of fire formation of dangerous gases possible.

In the event of fire the following can be released:

Sulphur dioxide (SO₂)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

6.3. Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale aerosols

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air.

Avoid effect of heat.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
67-63-0	propan-2-ol	8 hours	999	400	EH40/2005
		Short-term	1250	500	

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
67-63-0	propan-2-ol	500 mg/m3	DNEL long-term inhalative (systemic)	
		888 mg/kg bw/day	DNEL long-term dermal (systemic)	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	Colour	Odour
aerosol	black	like mineral oil

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.3

Spray on Grease with MoS₂

	Value	Temperature	at	Method	Remark
boiling point	not applicable				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 250 °C				
Self ignition temperature	not determined				
Lower explosion limit	0,6 Vol-%				
Upper explosion limit	3,2 Vol-%				
Vapour pressure	3,5 bar	20 °C			Doseninnendruck
Relative density	0,72 g/ml	20 °C			
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	not determined				
Solids content	29,1 %				
Oxidising properties	No information available.				
Explosive properties	The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .				
9.2. Other information	No information available.				

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

10.5. Incompatible materials**Substances to avoid**

Reactions with oxygen.

10.6. Hazardous decomposition productsSulphurous oxides (SO_x)**Thermal decomposition**

Remark No decomposition if used as directed.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
Skin irritation	low irritant effect - not necessary to label			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			

Experiences made from practice

Vapours may cause dizziness, headaches and tiredness

According to our experience and current information, the product has no detrimental effects on health if handled and used correctly

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information**12.1. Toxicity**

No information available.

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	The product is slightly degradable.			

12.3. Bioaccumulative potential



No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

15 01 01

15 01 10*

Name of waste

paper and cardboard packaging

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

General information

For proper waste disposal a complete emptying of the tin is necessary.

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable



Land and inland navigation transport ADR/RID

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 62,8 %

VOC value 410,9 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.2

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.