

No. 1907/2006 (REACH)
Printed 06.01.2016

revision 17.07.2015 (GB) Version 8.4

Contact CA-Primer for Polyolefines

! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Contact CA-Primer for Polyolefines

Code-Nr. 124500

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Primer to be used for plastics which are difficult to glue

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster Postbox 48045, DE-8460 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

GIZ Bonn (German, English) Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

Emergency advice -

Phone -

GIZ Bonn (Medizinische Auskunft in Deutsch und Englisch)

Tel: ++49(0)228-19 240

TRANSPORT: Consultank Lutz Harder GmbH Tel: +49(0)178

433 7434 (24h Emergency Contact)

SECTION 2: Hazards identification

Hazard classes and Hazard

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

categories	nazard Statements Classification procedure
Flam. Liq. 2	H225
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304

Hazard Statements Classification procedure



No. 1907/2006 (REACH) Printed 06.01.2016

revision 17.07.2015 (GB) Version 8.4

Contact CA-Primer for Polyolefines

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements

Classification procedure

categories

Aquatic Chronic 1 H410

Hazard Statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Very toxic to aquatic life with long lasting effects. H410

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]









GHS02

GHS07

GHS08

GHS09

Signal word

P370 + P378

P403 + P233

P403 + P235 P405

Danger

Hazard Statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Causes skin irritation. H315

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary State P102	ements Keep out of reach of children.
P210 P233 P243 P261 P264 P271 P273 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P310 P302 + P352 P303 + P361 + P353 P304 + P340 P312 P331 P332 + P313 P362	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing.

Store in a well-ventilated place. Keep container tightly closed.

In case of fire: Use foam for extinction.

Store locked up.

Store in a well-ventilated place. Keep cool.



No. 1907/2006 (REACH)
Printed 06.01.2016

revision 17.07.2015 (GB) Version 8.4

Contact CA-Primer for Polyolefines

P501

Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

n-heptane

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Primer solution (containing solvents) basing on heptane.

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
142-82-5	205-563-8	n-heptane	> 25	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Skin Irrit. 2, H315 / STOT SE 3, H336 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with water.

Refer to medical treatment.

In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Refer to medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.



No. 1907/2006 (REACH)
Printed 06.01.2016

revision 17.07.2015 (GB) Version 8.4

Contact CA-Primer for Polyolefines

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

Do not smoke when working.

Wash hands before breaks and after work.



No. 1907/2006 (REACH)
Printed 06.01.2016

revision 17.07.2015 (GB) Version 8.4

Contact CA-Primer for Polyolefines

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect of heat.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
142-82-5	n-heptane	8 hours	2085	500	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

! Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

AppearanceColourOdourliquidcolourlesssolvent-like

Odour threshold



No. 1907/2006 (REACH)
Printed 06.01.2016

revision 17.07.2015 (GB) Version 8.4

Contact CA-Primer for Polyolefines

not determined

Important health, safety and environmental information

Value Temperature at Method Remark

pH value not determined

boiling point ca. 95 °C

Melting point / Freezing

point

not determined

Flash point -4 °C closed cup

Vapourisation rate not determined

Flammable (solid) not determined

Flammability (gas) not determined

Ignition temperature 215 °C

Self ignition temperature not determined

Lower explosion limit 1,1 Vol-%

Upper explosion limit 6,7 Vol-%

Vapour pressure ca. 50 mbar 20 °C

Relative density ca. 0,7 g/cm3 20 °C

Vapour density not determined

Solubility in water immiscible

Solubility/other not determined

Partition coefficient noctanol/water (log P O/W) not determined

Decomposition temperature

not determined

Viscosity not determined

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated $\,$.

9.2. Other information

No information available.



No. 1907/2006 (REACH)
Printed 06.01.2016

revision 17.07.2015 (GB) Version 8.4

Contact CA-Primer for Polyolefines

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from heat.

Formation of explosive gas/air mixtures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition below 400°C.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

No toxical dates available.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Very toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.



No. 1907/2006 (REACH) Printed 06.01.2016

revision 17.07.2015 (GB) Version 8.4

Contact CA-Primer for Polyolefines

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1206	1206	1206
14.2. UN proper shipping name	HEPTANES	HEPTANES	Heptanes
14.3. Transport hazard class(es)	3	3	3
14.4. Packing group	II	II	II
14.5. Environmental hazards	Yes	Yes	Yes

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 3

tunnel restriction code D/E

Classification code F1

Marine transport IMDG

MARINE POLLUTANT

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

 VOC content
 97 %

 VOC value
 679 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



No. 1907/2006 (REACH)
Printed 06.01.2016

revision 17.07.2015 (GB) Version 8.4

Contact CA-Primer for Polyolefines

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.