

**! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Name of product**

CA-Aktivator Spray AC

Code-Nr. 125050

1.2. Relevant identified uses of the substance or mixture and uses advised against**Recommended intended purpose(s)**

to accelerate the curing of cyanacrylat adhesives.

1.3. Details of the supplier of the safety data sheet**Distributor**

WEICON GmbH & Co. KG

Königsberger Str. 255,, DE-48157 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de

Internet : www.weicon.de

Advice

Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0

E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer

WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Aerosol 1	H222, H229	
-----------	------------	--

Eye Irrit. 2	H319	
--------------	------	--

STOT SE 3	H336	
-----------	------	--

Hazard Statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS02



GHS07

Signal word

Danger

Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary Statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

acetone

Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Product has an anesthetic effect.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

3.2. Mixtures**Description**

Mixture of active ingredients with propellant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-64-1	200-662-2	acetone	50 <= 75	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
74-98-6	200-827-9	propane	10 <= 25	Flam. Gas 1, H220 / Press. Gas
99-97-8	202-805-4	N,N-dimethyl-p-toluidine	0,1 <= 0,3	Acute Tox. 3, H331 / Acute Tox. 3, H311 / Acute Tox. 3, H301 / STOT RE 2, H373 / Aquatic Chronic 3, H412
106-97-8	203-448-7	butane	10 <= 25	Flam. Gas 1, H220 / Press. Gas

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Take affected person into fresh air.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed**Physician's information / possible symptoms**

No relevant information available.

Physician's information / possible dangers

No relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed**Treatment (Advice to doctor)**

No relevant information available.



SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam

ABC powder

Carbon dioxide

Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

No relevant information available.

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

Use personal protective clothing.

For emergency responders

Ensure adequate ventilation.

6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

Ventilate area concerned

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Emergency telephone number: see section 1

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not spray into flames or any incandescent material.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

Take the usual precautions when handling with chemicals.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Keep away from food and drink.

Keep separated from food and feed.

**CA-Aktivator Spray AC**

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Pressurized container.

Do not pierce or burn even after use.

Protect from heat and sunlight.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Advice on storage compatibility

No relevant information available.

Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
67-64-1	Acetone	8 hours	1210	500	EH40/2005
		Short-term	3620	1500	
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
67-64-1	acetone	8 hours	1210	500	

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
67-64-1	acetone	186 mg/kg	DNEL long-term dermal (systemic)	
		1210 mg/m ³	DNEL long-term inhalative (systemic)	
		2420 mg/m ³	DNEL acute inhalative (local)	

PNEC

CAS No	Substance name	Value	Code	Remark
67-64-1	acetone	1,06 mg/l	PNEC aquatic, marine water	
		30,4 mg/kg	PNEC sediment, freshwater	
		10,6 mg/l	PNEC aquatic, freshwater	
		3,04 mg/kg	PNEC sediment, marine water	

**CA-Aktivator Spray AC****Additional advice**

The statutory local and national regulations have to be observed.

8.2. Exposure controls**Respiratory protection**

In case of insufficient ventilation or long-term effect use breathing apparatus.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

Hand protection

Gloves (solvent-resistant)

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification: Nitrile rubber

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

aerosol

Colour

colourless

Odour

typical, pungent

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
Acid number	not determined				
boiling point	not applicable				
melting point	not applicable				
Flash point	not applicable				
Vapourisation rate	not applicable				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	365 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	1,5 Vol-%				

**CA-Aktivator Spray AC**

	Value	Temperature	at	Method	Remark
Upper explosion limit	13 Vol-%				
Vapour pressure	8300 hPa	20 °C			
Relative density	0,673 g/cm ³	20 °C			
Vapour density	not determined				
Solubility in water					No or low immiscibility
Solubility/other	not determined				
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	99,8 %				
Solids content	0,1 %				

Oxidising properties

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No relevant information available.

10.2. Chemical stability

No dangerous decomposition products known.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No relevant information available.

10.5. Incompatible materials**Substances to avoid**

No relevant information available.

10.6. Hazardous decomposition products

No dangerous decomposition products known.

**Additional information**

No relevant information available.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	5800 mg/kg	rat		Information concerns to main component.
LD50 acute dermal	7800 mg/kg	rabbit		Informations concern to main component.
LC50 acute inhalation	20 mg/l (4 h)	rat		Informations concern to main component.
Skin irritation	No stimulation effect.			
Eye irritation	irritant			
Skin sensitization	non-sensitizing			

Additional information

The product was classified on the basis of the calculation procedure of the preparation directive (1999/45/EC).

SECTION 12: Ecological information**12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	8300 mg/l (96 h)			Information refers to the main component.
Daphnia	EC50 8800 mg/l	Daphnia magna		Information refers to the main component.

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Physico-chemical degradability	No relevant information available.			
Biological degradability	No relevant information available.			
Degradability	No relevant information available.			

12.3. Bioaccumulative potential

No relevant information available.

12.4. Mobility in soil

**CA-Aktivator Spray AC**

No relevant information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No relevant information available.

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Recommendations for the product**

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS (acetone)	AEROSOLS (acetone)	Aerosols, flammable (acetone)
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

14.6. Special precautions for user

Caution: Gases

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content 99,76 %

VOC value 671,4 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 1.3

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H412	Harmful to aquatic life with long lasting effects.