

No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

## ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Primer S 300

Code-Nr. 135503

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

to be used as surface preconditioning

1.3. Details of the supplier of the safety data sheet

**Distributor** WEICON GmbH & Co. KG

Königsberger Str. 255,, DE-48157 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Flam. Liq. 3 H226
Skin Irrit. 2 H315
Skin Sens. 1 H317
STOT SE 3 H335, H336
Aquatic Chronic 2 H411

#### **Hazard Statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]







GHS02

GHS07

GHS09

### Signal word

Warning

#### **Hazard Statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

## **Precautionary Statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

P353 water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing.

P363 Wash contaminated clothing before reuse. P370 + P378 In case of fire: Use dry sand to extinguish.

P391 Collect spillage.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container to hazardous or special waste collection point.

#### Hazardous ingredients for labeling

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers, Hydrocarbons, C9, arom. hydrotreater (-)



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

## Special rules for supplemental label elements for certain mixtures

Contains isocyanates. May produce an allergic reaction.

#### 2.3. Other hazards

#### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

not applicable

#### 3.2. Mixtures

#### Description

Compound

#### **Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
53880-05-0	500-125-5	3-Isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate, oligomers	> 20	Skin Sens. 1, H317
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom. Low boiling point naphtha - unspecified	1 < 20	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / Skin Irrit. 2, H315 / STOT SE 3, H336 / Aquatic Chronic 2, H411
		Hydrocarbons, C9,arom. hydrotreater (-)	2,5 < 5	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335, H336 / Aquatic Chronic 2, H411

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

## In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

## In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

## In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

#### In case of ingestion

Seek medical advice.

Do not induce vomiting.

Rinse out mouth thoroughly with water.

# 4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms

vomiting

Respiratory complaints

Headache

Allergic symptoms

Nausea

skin irritation



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

## 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

## Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

### Unsuitable extinguishing media

Full water jet

#### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen gases (NOx)

Carbon monoxide (CO)

Carbon dioxide (CO2)

#### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

#### **Additional information**

Cool endangered containers with water spray jet.

Collect contaminated firefighting water separately, must not be discharged into the drains.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

## For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

#### 6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

Collect contaminated water / firefighting water separately.

Do not discharge into the drains/surface waters/groundwater.

#### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

#### **Additional Information**

Sort out leaky cans and dispose according to regulations.

#### 6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

#### General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

#### Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Protect from heat and sunlight.

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Prevent penetration into the ground.

Keep only in original container.

## Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

## Further information on storage conditions

Store closed container at cool and aired place.

Protect from frost.

Protect from heat and direct solar radiation.

Store in a dry place.

## 7.3. Specific end use(s)

#### Recommendation(s) for intended use

See section 1.2

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Additional advice**

The statutory local and national regulations have to be observed.

#### 8.2. Exposure controls

#### Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, filter A

## Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

AppearanceColourOdourviscousyellowishsolvent-like

Odour threshold not determined

Important health, safety and environmental information

Method Value Temperature at Remark pH value not determined not determined boiling point melting point not determined 47 °C Flash point not determined Vapourisation rate Flammable (solid) not determined Flammability (gas) not determined not determined Ignition temperature not determined Self ignition temperature not determined Lower explosion limit **Upper explosion limit** not determined not determined Vapour pressure 20 °C 1 g/cm3 Relative density Vapour density Solubility in water insoluble Organic Solubility/other soluble solvent not determined Partition coefficient noctanol/water (log P O/W)



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

Value Temperature at Method Remark

Decomposition not determined temperature

Viscosity dynamic not determined

Viscosity kinematic not determined

#### **Oxidising properties**

No information available.

#### **Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

#### 9.2. Other information

No information available.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

No information available.

#### 10.3. Possibility of hazardous reactions

No information available.

## 10.4. Conditions to avoid

Keep away from heat.

#### 10.5. Incompatible materials

No information available.

## 10.6. Hazardous decomposition products

Nitrous gases Carbon monoxide Carbon dioxide Toxic gases/vapours

## Thermal decomposition

Remark No decomposition if used as directed.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

## Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5000 mg/kg	rat	OECD 401	CAS: 53880-05-0
LD50 acute dermal	> 2000 mg/kg	rabbit	OECD 402	CAS: 64742-95-6
LC50 acute inhalation	> 5,01 mg/l (4 h)	rat	OECD 403	CAS: 53880-05-0



No. 1907/2006 (REACH) Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

	Value/Validation	Species	Method	Remark			
Skin irritation	irritant	rabbit	OECD 404				
Eye irritation	non-irritant	rabbit eye	OECD 405				
Skin sensitization	sensitizing						
Subacute Toxicity - 0	Subacute Toxicity - Carcinogenicity						
	Value	Species	Method	Validation			
Mutagenicity				No mutagenity, after different in-vitro studies.			
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.			
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.			

## Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

## **Experiences made from practice**

Often and long skin contact may cause degreasing and desiccation of the skin which may caus skin irritation.

Vapours may cause dizziness, headaches and tiredness

Sensitization through skin contact possible.

Irritates respiratory tract.

Frequent persistent contact with the skin may cause skin irritation.

## **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

	. 4 : -	-   : -	al effect	-،
-cc	TOYIC	ninnir	ai etteri	

	Value	Species	Method	Validation
Fish	LC50 10 mg/l (96 h)	Oncorhynchus myki	iss OECD 203	CAS: 64742-95-6
Daphnia	EC 50 4,5 mg/l (48 h)	Daphnia magna	OECD 202	CAS: 64742-95-6
Algae	EC50 3,1 mg/l (72 h)	Pseudokirchneriella subcapitata	OECD 201	CAS: 64742-95-6
12.2. Persist	ence and degradability Elimination rate	Method of analysis	Method	Validation
Biological	77,05 % (28 d)		OECD 301 F	not readily degradable

## CAS: 64742-95-6

12.3. Bioaccumulative potential Slight bioaccumulation potential.

12.4. Mobility in soil

degradability



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

## **General regulation**

Toxic to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Waste code No.

#### Name of waste

08 01 11\* 15 01 10\* waste paint and varnish containing organic solvents or other hazardous substances packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

#### Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

#### Recommendations for packaging

Dispose of according to the local waste regulations.

#### **General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL ((MESITYLEN, Solvent naphtha (petroleum)))	Paint related material
14.3. Transport hazard class(es)	3	3	3
14.4. Packing group	III	III	III
14.5. Environmental hazards	Yes	Yes	Yes

### 14.6. Special precautions for user

No information available.

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

Primer S 300

#### Land and inland navigation transport ADR/RID

Hazard label(s) 3 tunnel restriction code D/E Special provisions 640E Classification code F1

#### **Marine transport IMDG**

MARINE POLLUTANT

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC** standard

 VOC content
 78 %

 VOC value
 803,4 g/L

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

#### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335, -?-

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.