

No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

**Plastic Cleaner** 

### ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Plastic Cleaner Code-Nr. 152040

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

**Technical Liquids** 

1.3. Details of the supplier of the safety data sheet

**Distributor** WEICON GmbH & Co. KG

Königsberger Str. 255,, DE-48157 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322 - 244

E-Mail : msds@weicon.de Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard Hazard Statements Classification procedure categories

Hazard Statements Classification procedure

Hazard Statements Classification procedure

Fiam. Liq. 2 H225
Skin Irrit. 2 H315
STOT SE 3 H336
Asp. Tox. 1 H304
Aquatic Chronic 2 H411

**Hazard Statements** 

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

### **Plastic Cleaner**

H411

Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

## Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]









GHS02

GHS07 GHS08

8 GHS09

### Signal word

Danger

P102

#### **Hazard Statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Keep out of reach of children.

### **Precautionary Statements**

	·
P210 P220 P233 P234 P243 P261 P264 P271 P273 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep/Store away from clothing. Keep container tightly closed. Keep only in original container. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P310 P302 + P352 P303 + P361 + P353 P304 + P340 P312 P331 P332 + P313 P362 P370 + P378 P391	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing. In case of fire: Use foam for extinction. Collect spillage.
P403 + P233 P403 + P235 P405 P420	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Store away from other materials.
P501	Dispose of contents/container to hazardous or special waste collection point.

### Hazardous ingredients for labeling

Naphtha (petroleum), hydrotreated light, pentane



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

**Plastic Cleaner** 

### Special rules for supplemental label elements for certain mixtures

Contains (R)-(+)-Limonene . May produce an allergic reaction.

#### 2.3. Other hazards

Product has an anesthetic effect.

#### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

not applicable

#### 3.2. Mixtures

#### Description

Compound

#### **Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
109-66-0	203-692-4	pentane	10 < 25	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 2, H411
5989-27-5	227-813-5	(R)-p-mentha-1,8-diene	<= 0,1	Flam. Liq. 3, H226 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Acute 1, H400 / Aquatic Chronic 1, H410
64742-49-0	921-024-6	Naphtha (petroleum), hydrotreated light	50 < 75	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Aquatic Chronic 2, H411 / Skin Irrit. 2, H315 / STOT SE 3, H336
64-17-5	200-578-6	ethanol	3 < 10	Flam. Liq. 2, H225 / Eye Irrit. 2, H319
REACH				
CAS No	Name			REACH registration number
5989-27-5	(R)-p-mentha	a-1,8-diene		01-2119529223-47
64742-49-0	Naphtha (pet	roleum), hydrotreated light		01-2119475514-35
64-17-5	ethanol			01-2119457610-43
less than 5 9		ccording to regulation (EC) No 648/2004, and opening to regulation	annex VII	

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

### **General information**

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.

#### In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

**Plastic Cleaner** 

#### In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Call for a doctor immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

#### Physician's information / possible symptoms

Unconsciousness

Coughing

Respiratory complaints

Headache

Confusion

skin irritation

## 4.3. Indication of any immediate medical attention and special treatment needed

#### Treatment (Advice to doctor)

If swallowed or in the event of vomiting, risk of entering the lungs.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

### Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

water mist

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

#### **Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

## **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

**Plastic Cleaner** 

#### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Ventilate area concerned

After taking up the material dispose according to regulation.

#### 6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

#### General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

### Hygiene measures

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Avoid effect of heat.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in closed original container.

### Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

### Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

### 7.3. Specific end use(s)

### Recommendation(s) for intended use

See section 1.2

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
64-17-5	ethanol	8 hours	1920	1000	EH40/2005
67-56-1	methanol	8 hours Short-term	266 333	200 250	EH40/2005



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

**Plastic Cleaner** 

2035 mg/m3 DNEL long-term inhalative (systemic)

		/04/000/EEO 0000/00/EO	:. 2006/15/EC or 2009/161/EU)
Indicative occupational	LAYNOSIIRA IIMIT VAIIIAS	(91/322/FFC, 2000/39/FC	. 2006/15/EC. Or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
109-66-0 DNEL-/PNEC		8 hours	3000	1000	
CAS No	Substance name	Value	Code		Remark
64742-49-0	Naphtha (petroleum), hydrotreated light	773 mg/kg bw/day	DNEL long-term derma	(systemic)	

### **DNEL Consumer**

CAS No	Substance name	Value	Code	Remark
64742-49-0	Naphtha (petroleum), hydrotreated light	699 mg/kg bw/day	DNEL long-term oral (repeated)	
		608 mg/m3	DNEL long-term inhalative (systemic)	
		699 mg/kg bw/day	DNEL long-term dermal (systemic)	

#### **Additional advice**

The statutory local and national regulations have to be observed.

### 8.2. Exposure controls

#### **Respiratory protection**

Filter A or environment-independent breathing apparatus

Breathing apparatus in the event of aerosol or mist formation.

#### **Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

### Eye protection

tightly fitting goggles

#### Other protection measures

protective clothing

### Appropriate engineering controls

Sufficient ventilation and exhaustion.

### **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

AppearanceColourOdourliquidcolourless, clearcharacteristic

**Odour threshold** 



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

**Plastic Cleaner** 

not determined

Important health, safety and environmental information

Value Temperature at Method Remark

pH value not determined

boiling range 36 °C

melting point not determined

Flash point -35 °C

Vapourisation rate not determined

Flammable (solid) not applicable

Flammability (gas) not applicable

Ignition temperature 200 °C

Self ignition temperature

The product is not

self-igniting.

Lower explosion limit 0,8 Vol-%

Upper explosion limit 15 Vol-%

**Vapour pressure** 573 hPa 20 °C

Relative density 0,71 g/cm3 20 °C

Vapour density not determined

Solubility in water

No or low immiscibility

Solubility/other not determined

Partition coefficient noctanol/water (log P O/W) not determined

Decomposition temperature

not determined

Viscosity dynamic not determined

Viscosity kinematic not determined

Solvent content 100 %

## **Oxidising properties**

No information available.

### **Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

### 9.2. Other information

No information available.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

**Plastic Cleaner** 

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

No information available.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known.

#### 10.4. Conditions to avoid

Keep away from heat.

### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

#### Thermal decomposition

Remark No decomposition if used as directed.

### **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 5840 mg/kg	rat		Naphtha
LD50 acute dermal	> 2920 mg/kg	rabbit		Naphtha
LC50 acute inhalation	> 25 mg/l (4 h)	rat		Naphtha
Skin irritation	irritant			
Eye irritation	non-irritant			
Skin sensitization	non-sensitizing			

## **Experiences made from practice**

Often and long skin contact may cause degreasing and desiccation of the skin which may caus skin irritation.

Swallowing may cause vomiting and diarrhoea.

Frequent persistent contact with the skin may cause skin irritation.

Irritates mucous membranes.

Inhalation causes narcotic effect/intoxication.

#### **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

**Plastic Cleaner** 

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

_			
HCO1	けいといい	ורמוראו	effects
	CAIC	Jiogica	CHOOLS

· ·	Value	Species	Method	Validation
Fish	LL/EL/IL50 11,4 mg/l (96 h)	Oncorhynchus mykiss		Naphtha
Daphnia	LL/EL/IL50 3 mg/l (48 h)	Daphnia magna		Naphtha
Algae	LL/EL/IL50 30 - 100 mg/l (72 h)	Pseudokirchneriella subcapitata		Naphtha

### 12.2. Persistence and degradability

No information available.

#### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Other adverse effects

### **General regulation**

Toxic to aquatic life, fishes and plankton.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

### Recommendations for the product

Remove in accordance with local official regulations.

### Recommendations for packaging

Dispose of according to the local waste regulations.

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1993	1993	1993
14.2. UN proper shipping name	FLAMMABLE LIQUID, N.O. S. (Naphtha (petroleum), Pentan Mixture)	FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), Pentane mixture)	Flammable liquid, n.o.s. (Naphtha (petroleum), Pentane mixture)
14.3. Transport hazard class(es)	3	3	3
14.4. Packing group	I	1	I



No. 1907/2006 (REACH)
Printed 02.09.2016

revision 03.08.2016 (GB) Version 8.4

### **Plastic Cleaner**

	ADR/RID	IMDG	IATA-DGR
14.5. Environmental hazards	Yes	Yes	Yes

#### 14.6. Special precautions for user

Caution: FLAMMABLE LIQUID

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

### Land and inland navigation transport ADR/RID

Hazard label(s) 3 tunnel restriction code D/E Classification code F1

#### **Marine transport IMDG**

MARINE POLLUTANT

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC** standard

 VOC content
 100 %

 VOC value
 709 g/L

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

#### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Danish MAL-code: 5-3

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effect