

# **Corro-Protection**

**Technical Datasheet** 

Create Date: 06.06.2016 - Page 1/1



defects in accordance with and subject to our General Sales Conditions. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

### **Health and Safety**

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Corrosion protection for indoor storage and overseas shipment of metals

WEICON protective film approved by the German TÜV. It lastingly preserves tools and precision components with a dry and waxy layer.

WEICON Corro Protection can be used as safe corrosion protection for bare, unpainted metal parts, for the indoor storage of work-pieces, as corrosion protection during overseas transport and for the conservation of tools and precision components. The protective layer can be removed easily (e.g. with WEICON Cleaner S).

### **Technical data**

Colour	opaque
Odour	solvent
Temperature resistance	-20 up to +80 °C
Shelf life min.	24 months
Special features	RWTÜV-tested, wax-based
Suitable for use with	WSD 400 und WPS 1500 (Material gut aufrühren)

### **Processing**

Clean and degrease surfaces with WEICON Cleaner S (liquid or spray). Spray Weicon Corro-Protection (as aerosol) on the parts. Bring Weicon Corro-Protection (in form of a technical liquid in a canister) to room temperature, mix it to a homogeneous liquid and apply it with a brush on the parts to be protected.

The material is finally cured after approx. 3-4 hours with room temperature. To obtain a higher corrosion protection, several layers can be applied. The protective layer can be removed with WEICON Cleaner S (liquid or spray).

### Storage

Keep in closed original container. Protect from direct solar radiation. Storage temperature may not exceed  $+50\,^{\circ}\text{C}$ .

Store container at cool and aired place. Store in a dry place.

### Note

Any product specifications and recommendations given herein must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do warrant the continuously high quality of our products being free from

# WEICON GmbH & Co. KG (Headquarter)

Königsberger Str. 255 · DE-48157 Münster P.O. Box 84 60 · DE-48045 Münster Germany

Tel. +49 (0) 251 / 93 22-0 Fax +49 (0) 251 / 93 22-244 Fax +49 (0) 251 / 93 22-233 Export www.weicon.de · info@weicon.de

### WEICON Middle East L.L.C.

Jebel Ali Ind Area 3 · P.O. Box 118 216 Dubai · U.A.E

Phone +971 4 880 25 05 Fax +971 4 880 25 09 Mobile +971 50 545 99 83 www.weicon.ae · info@weicon.ae

### WEICON Inc.

20 Steckle Place · Unit 20 Kitchener · Ontario · N2E 2C3

Phone +1 519 896 5252 Fax +1 519 896 5254 Cell +1 519 590 5168 www.weicon.ca · info@weicon.ca

## WEICON Kimya Sanayi Tic. Ltd. Şti.

Yenibosna Mahallesi Yalçın Koreş Caddesi Arifağa Sokak No: 29 Kat: 3 34530 Yenibosna – Istanbul Turkey www.weicon.biz.tr · info@weicon.biz.tr

### WEICON Romania SRL

Str. Podului Nr.1 547176 Budiu Mic (Targu Mures) www.weicon.com · office@weicon.com